


REV	DESCRIPTION	DATE	APPROVED
A	新板发行	2020. 11. 06	HHM

NOTE:

1. MATERIAL:
 - 1.1 INSULATOR:HIGH TEMPERATURE PLASTIC
 - 1.2 CONTACT:BRONZE
 - 1.3 SHELL:BRASS & K7 & SPCC
2. ELECTRICAL CHARACTERISTICS;
 - 2.1 CONTACTRESISTANCE:30mΩ MAXIMUM
 - 2.2 CONTACT CURRENT RATING:1.5A
 - 2.3 DIELECTRIC WITHSTANDING VOLTAGE:100 V AC R.M.S.
 - 2.4 INSULATION RESISTANCE 100 MEGOHMS MIN
 - 2.5 OPERATING TEMPEROTURE:-40° C ~ 85° C
- 3 MECHANICAL CHARACTERISTICS:
 - 3.1 MATING FORCE:3.57kgf MAX
 - 3.2 UNMATED FORCE:0.82kgf MIN AFTER TEST
 - 3.3 DURABILITY MANDATORY:5,000 CYCLES
4. PLATING
 - 4.1 TERMINAL:
 - 50u" MIN NICKEL ALL OVER
 - 80u"MIN Tin ON SOLDER AREA
 - (1~30)u"Au ON CONTACT AREA
 - 4.2 SHELL:100u"MIN. NICEL ALL OVER

CUSTOMER DRAWING			铭创科技（东莞）有限公司 Mingchuang Technology (Dongguan) Co., Ltd.		
UNITS mm	SCALE 1:1	SHEET			
PROJECTION: 		DRAW: DAP	TITLE USB AF 3.0板上四脚插板SMT 90度 L=14.25 卷边		
GENERAL TOLERANCE 0. ±0.50 0.0 ±0.30 0.00 ±0.20 0. ° ±3° 0.0° ±2°		CHECK: HWT			
		APPD: HHM	MAT'L SEE TABLE		FINISH SEE TABLE
			DWG. NO. 0717.3AF.BS.Z9		PART NO. _____ SIZE A4