


RECOMMENDED P.C.B. LAYOUT
TOLERANCE UNSPECIFIED $\pm 0.05\text{mm}$



REV
A

DESCRIPTION
新板发行

DATE
2022. 07. 16

APPROVED
HHM

- ELECTRICAL:
CURRENT:15A
CONTACT RESISTANCE:40 MILLIOHMS MAX
DIELECTRIC WITHSTANDING VOLTAGE: 200V AC
INSULATION RESISTANCE:100 MEGOHMS MIN
- MECHANICAL:
MATING FORCE:6-20N
WITHDRAWAL FORCE:5-20N
DURBILITY:10000 CYCLES
- ENVIRONMENTAL:
TEMPERTURE RANGE $-40^{\circ}\sim 105^{\circ}$
SALT TESTING:48 HOURS

7				
6				
5				
4	TYPE C MD	HIGH TEMP	BLACK	UL 94V-0
3	CENTER PIECE	STAINLESS STEEL	—	NO Plated
2	TYPE C TERMINAL	COPPER ALLOY	—	Gold Plated
1	SHELL	COPPER ALLOY	—	Ni Plated
NO.	DESCRIPTION	MATERIAL	COLOR	REMARK

CUSTOMER DRAWING

UNITS mm	SCALE 1:1	SHEET 1 OF 1
PROJECTION: 	DRAW: DAP	
GENERAL TOLERANCE 0. ± 0.50 0.0 ± 0.30 0.00 ± 0.15 0.° $\pm 2^{\circ}$ 0.0° $\pm 1^{\circ}$	CHECK: HWT	
	APPD: HHM	

铭创科技（东莞）有限公司 Mingchuang Technology (Dongguan) Co., Ltd.			
TITLE TYPE C母座16PIN 15A大电流 板上四脚全贴SMT L=7.35			
MAT'L SEE TABLE		FINISH SEE TABLE	
DWG. NO. 0953. TCF. 16BS. H5	PART NO.		SIZE A4