








NOTE:
备 注:
1.MATERIAL SPECIFICATION:
1.材料规格:
1-1.HOUSING:HIGH TEMPERATURE RESISTANT PLASTIC,UL94 V-0.
1-1.胶芯材料: 高温塑胶, 防火等级UL94 V-0
1-2.TERMINAL: COPPER ALLOY
1-2.端子材料: 铜合金
1-3.FRONT SHELL: STAINLESS STEEL
1-3.外壳材料: 不锈钢
1-4.MID PLATE: STAINLESS STEEL
1-4.中夹片: 不锈钢
2.PLATING SPECIFICATION:
2.电镀规格:
2-1.TERMINAL:
2-1.端子:
Ni 50u" MIN. UNDER PLATED OVER ALL.
镀镍底 50u" MIN.
Au PLATED 0.5~1u" OVER Ni
表面刷金0.5~1u"
2-2.FRONT SHELL:
2-2.外壳:
Ni 50u" MIN. PLATED OVER ALL.
镀镍底 50u" MIN.
3.MECHANICAL PERFORMANCE,
3.机械性能,
3-1.INSERTION FORCE: 0.5~2.0kgf.
3-1.插入力: 0.5~2.0kgf.
3-2.REMOVAL FORCE: 0.6kgf~2.0kgf.
3-2.拔出力: 0.6kgf~2.0kgf.
3-3.DURABILITY: 10000 CYCLES.
3-3.插拔寿命: 10000次.
4.ELECTRICAL PERFORMANCE,
4.电气性能,
4-1. VOLTAGE RATING: 5.0V DC/AC
4-1. 额定电压: 5.0V DC/AC
CURRENT RATING: 2.0A
额定电流: 2.0A
4-2. LLCR: 50mΩ/PIN MAX.
4-2. 接触阻抗: 50mΩ/PIN MAX.
4-3.INSULATION RESISTANCE: 100MΩ MIN
4-3. 绝缘阻抗: 100MΩ MIN
4-4.DIELECTRIC WITHSTAND VOLTAGE,AC 100V FOR 1 MINUTE.
4-4. 耐电压: AC 100V FOR 1 MINUTE.
5. ENVIRONMENTAL PERFORMANCE:
5. 环境特性:
OPERATING TEMPERATURE: -25°C~+85°C.
工作温度: -25°C~+85°C.



RECOMMEND P.C.B LAYOUT(COMPONENT SIDE)
TOLERANCE FOR PCB LAYOUT IS ± 0.05



CUSTOMER DRAWING			铭创科技（东莞）有限公司		
UNITS mm	SCALE 1:1	SHEET			
PROJECTION: 		DRAW: DAP	TITLE TYPE C母座16PIN 板上四脚插板SMT L=6.5		
GENERAL TOLERANCE 0. ±0.30 0.0 ±0.20 0.00 ±0.10 0.° ±10° 0.0° ±8°		CHECK: HWT			
		APPD: HHM	MAT' L SEE TABLE		FINISH SEE TABLE
			DWG. NO. 1601. TCF. 16BS. H97		PART NO. _____ SIZE A4

铭创科技（东莞）有限公司

TITLE
TYPE C母座16PIN 板上四脚插板SMT L=6.5

MAT'L	FINISH
SEE TABLE	SEE TABLE

DWG. NO. 1601. TCF. 16BS. H97	PART NO. _____	SIZE A4
----------------------------------	-------------------	------------